## Ready-n-Weigh Bench Scale System CW-90XB Scale Base 480/480 Plus Indicator





### **Standard Features**

- Package includes scale with IP69K stainless steel hermetically sealed load cell with an indicator and 12-inch column
- Factory calibrated with indicator setup and configured for 5,000 divisions
- Scale includes rubber feet to provide exceptional traction and avoid scratching surfaces along with removable top cover for ease of cleaning
- AC power 100 to 240 VAC
- Numeric keypad (480 plus)





Measurement Canada Approved

- Battery backed time and date
- Standard RS-232 serial ports for connecting to peripherals



WARNING: Cancer and Reproductive Harm California Proposition 65

## Complete Bench Scale Package with CW-90XB Light-capacity Bench Scale and 480/482 Legend<sup>®</sup> Series Indicator

Rice Lake's CW-90XB light-capacity bench scale is made with an IP69K stainless steel hermetically sealed load cell and 304 stainless steel construction. This bench scale meets HACCP requirements and is engineered according to sanitary design principles. The CW-90XB is available in capacities up to 100 pounds.

This package pairs the 480 Legend Series digital weight indicator with the CW-90XB. Rice Lake's 480 has a 0.8-inch 6-digit LED display, NEMA Type 4X/IP66 stainless steel washdown enclosure and programmable ticket formats for gross, net, accumulator and setpoints.

This package can also pair the 480 Legend Series digital weight indicator with the CW-90XB. Rice Lake's 480 has a 0.8-inch 6-digit LED display, NEMA Type 4X/IP66 stainless steel washdown enclosure and programmable ticket formats for gross, net, accumulator and setpoints.

### **CW-90XB Bench Scale Specifications**

Load Cell, NTEP Certified: IP69K stainless steel and hermetically sealed

Scale Construction: 304 stainless steel

Maximum Overload: 180% to 200% depending on capacity

**Overload Protection:** Five-point, independently adjusted Scale Frame: AISI304L, straight line finish, Ra = 45 ±10

Scale Cover: AISI304L, straight line finish,  $Ra = 45 \pm 10$ 

Cable Length: 34 in Temperature: Compensated:

14 °F to 104 °F (-10 °C to 40 °C)

CW-90XB Approvals:

NTEP CC 95-072, Class III 5,000 d Measurement Canada AM-5082 Load cell is FM approved

Warranty: Three-year limited (includes water ingress)

### 480/480 Plus Indicator Specifications

#### **Communication Ports:**

Com 1: RS-232 full duplex Com 2: RS-232 full duplex or 20 mA simplex, continuous Both ports 1200, 2400, 4800, 9600, 19200, 38400 baud seven or eight data bits, even, odd or no parity

#### Display:

LED display 0.8 in (20 mm), six-digit, seven-segment

**Status Annunciators:** Gross, net, center of zero, standstill, Ib, kg, tare, preset tare

**Keys/Buttons:** Flat membrane panel, embossed keys, tactile feel **Rating/Material:** 


Enclosure: NEMA Type 4X/IP66, heavy-gauge stainless steel


#### **Approvals:**

NTEP 12-123 Measurement Canada AM-5892C CE Marked cULus Listed

Warranty: Two-year limited

# **CW-90XB Ready-n-Weigh Bench Scale System Dimensions**





CW-90XB with 480 indicator

480/480 Plus				
10 × 10 in				
А	19.50 in	E	9.25 in	
В	10.25 in	F	4.25 in	
с	14.53 in	G	10.25 in	
D	13.25 in			
12 × 12 in				
А	19.50 in	E	9.25 in	
В	12.25 in	F	4.25 in	
с	16.53 in	G	12.25 in	
D	13.25 in		Note: 1 in = 25.4 mm	

### Parts

Part #	Description			
480 Package 115 VAC, LED, US Plug-Type B				
201241	Scale PKG, CW-90XB-480 10x10 5 lb/2.5 kg with 12 inch column 115VAC SST			
201242	Scale PKG, CW-90XB-480 10x10 10 lb/5 kg with 12 inch column 115VAC SST			
201243	Scale PKG, CW-90XB-480 10x10 25 lb/10 kg with 12 inch column 115VAC SST			
201244	Scale PKG, CW-90XB-480 12x12 25 lb/10 kg with 12 inch column 115VAC SST			
201245	Scale PKG, CW-90XB-480 12x12 50 lb/25 kg with 12 inch column 115VAC SST			
201246	Scale PKG, CW-90XB-480 12x12 100 lb/50 kg with 12 inch column 115VAC SST			
480 Package 90-264 VAC, LED, Euro Plug-Type E				
201254	Scale PKG, CW-90XB-480 10x10 5 lb/2.5 kg with 12 inch column 90-264VAC SST			
201255	Scale PKG, CW-90XB-480 10x10 10 lb/5 kg with 12 inch column 90-264VAC SST			
201257	Scale PKG, CW-90XB-480 10x10 25 lb/10 kg with 12 inch column 90-264VAC SST			
201258	Scale PKG, CW-90XB-480 12x12 25 lb/10 kg with 12 inch column 90-264VAC SST			
201259	Scale PKG, CW-90XB-480 12x12 50 lb/25 kg with 12 inch column 90-264VAC SST			
201260	Scale PKG, CW-90XB-480 12x12 100 lb/50 kg with 12 inch column 90-264VAC SST			
480 Plus Package 115 VAC, LED, Numeric keypad, US Plug-Type B				
201247	Scale PKG,CW-90XB-480Plus 10x10 5 lb/2.5 kg with 12 inch column 115VAC SST			
201248	Scale PKG,CW-90XB-480Plus 10x10 10 lb/5 kg with 12 inch column 115VAC SST			
201249	Scale PKG,CW-90XB-480Plus 10x10 25 lb/10 kg with 12 inch column 115VAC SST			
201250	Scale PKG,CW-90XB-480Plus 12x12 25 lb/10 kg with 12 inch column 115VAC SST			
201251	Scale PKG,CW-90XB-480Plus 12x12 50 lb/25 kg with 12 inch column 115VAC SST			
201253	Scale PKG,CW-90XB-480Plus 12x12 100 lb/50 kg with 12 inch column 115VAC SST			
480 Plus Package 90-264 VAC, LED, Numeric keypad, Euro Plug-Type E				
201261	Scale PKG,CW-90XB-480Plus 10x10 5 lb/2.5 kg with 12 inch column 90-264VAC SST			
201262	Scale PKG,CW-90XB-480Plus 10x10 10 lb/5 kg with 12 inch column 90-264VAC SST			
201263	Scale PKG,CW-90X-480Plus 10x10 25 lb/10 kg with 12 inch column 90-264VAC SST			
201264	Scale PKG,CW-90XB-480Plus 12x12 25 lb/10 kg with 12 inch column 90-264VAC SST			
201265	Scale PKG,CW-90XB-480Plus 12x12 50 lb/25 kg with 12 inch column 90-264VAC SST			

201266 Scale PKG,CW-90XB-480Plus 12x12 100 lb/50 kg with 12 inch column 90-264VAC SST

# www.ricelake.com | 800-472-6703

An ISO 9001 Registered Company ©2024 Rice Lake Weighing Systems